

CDSVAN

Digital Interpreter Console DOLV



Description

The DOLV is a digital interpreter console for one interpreter with a modern and sophisticated design. It's clearly arranged controls, its large, bright display and the illuminated buttons allow straight and intuitive operation. All common (mono and stereo) headphones can easily be connected to the console and in combination with various microphone types it guarantees maximum comfort for the interpreter. The DOLV also allows the use of headsets and complies to international standards.

The interpreter console is divided into 4 sections:

Monitoring section

Loudspeaker with integrated channel selector to monitor all languages. The Loudspeaker will automatically be muted, when a DOLV in one booth gets live.

Listening and relay section

It is possible to create up to 5 relay channels separately, in order to be able to react in combination with the source language fast to different conference situations. All occupied channels are indicated clearly in the display.

User controls and indications:

- Original / Floor button
- five relay channels, pre-selectable
- rotary knobs for Volume, bass/ treble control and channel program
- LED "Hearing guard"

Speaking section

- up to three outgoing channels (A/B/C)
- microphone ON/ OFF button
- Mute - button to mute the activated language channel temporarily

Additional features

- message signal for incoming messages, to be shown on the display
- Operator and/ or Chairman call
- speak slow function
- Help function
- repeat original function
- adjustable viewing angle (25/35 degrees)

Via the CDSVAN software, different modes can be selected; e.g.:

- interpreter survey
- active Take over
- Auto Floor/ relay
- Save/ load presets for different configurations
- local and central console pre-configuration

Main features

- up to 32 channels (Floor + 31 languages)
- modern and sophisticated design with braille engraving
- no interference with mobile phones, WLAN and bluetooth
- five pre-selectable Relay channels and one Original
- number of DOLV in one booth is unlimited
- high quality audio, above the CD-audio standard

Technical Data

Complies with the standards IEC914 and IEC2603.2

- Sample rates: 32kHz, 44.1kHz and 48kHz
- Frequency response: 20kHz
- Resolution: up to 24 BIT
- LC-Display, 2 x 56 characters, backlit

Connections

- PREVIOUS (RJ45-socket) for interconnection
- NEXT (RJ45-socket) for interconnection
- Microphone TM58/6 (Minicon socket)
- Headphones (3.5mm and 6.3mm jack-socket)
- Electret Headset (DIN-socket)

Housing

- Lower part: robust plastic, grey
- Operation panel: aluminium, "silver" anodized
- WxHxD: (305 x 90 x 175)mm
- Weight: 1.5 kg

Accessories (not included in delivery)

- **TM58/6** Conference Microphone (01.0560)
- **TM58/6-500** Conference Microphone 500mm (01.0561)
- **TM58/6S** Conference Microphone silver painted (01.0562)
- **TM58/6-2S** Conference Microphone with 2 goosenecks (01.0560.S2)
- **K45/7** Conference Headphone (03.0280)
- **K45/16** Dynamic Headphone with 1.5m cable (03.0290)
- **PMX60** Dynamic Conference Headphone with neckband (03.5501)
- **HS394** Lightweight Interpreter Headset (03.5530)
- **HS460** Professional Interpreter Headset (03.5540)