

PRODUCT INFORMATION DV-200

Delegate Unit



Description

For microphone operating modes PABC, AUT, MAN, PAPB and 5 keys for voting and audience response procedures. Regardless of where delegates are seated, they can be identified via integrated ChipCard readers incorporating attendance checks, audience-response procedures and similar activities. An individual MESSAGE LED enables each delegate to be contacted where he is seated. The priority function (PRIO) for allocation to the microphone of the chief organizer can be allocated via software. As an optional extra, the unit is available with only three keys for voting or with a software-defined special function key.

Technical Data

Complies with internat. standard EIC914
Frequency response: 125Hz - 12.5kHz, signal-to-noise ratio: >70dBA, distortion factor: <0.5%
5 keys for votes and evaluations, microphone key on/off/request for the floor
Integrated ChipCard reader, loudspeaker, LEDs
VOTE NOW, MIC, REQUEST, MESSAGE, BADGE
Connector socket R7 standard for microphones TM55/5; connecting cable: permanently attached, length 2.5m, plug standard S8G-CF; S8G-CF socket for connecting further delegate units
Dimensions: width 190/178, height 29/59, depth 140mm
Weight including cable: 720g;
plastic housing
colour: black

BRÄHLER ICS is committed to continually improving its products and so reserves the right to make technical modifications without notice.

WPF.04.0590.E.020821