

Visual Conferencing

DIGIMIC lean⁺ conference technology
with high-tech retractable monitor.

brähler
SYSTEMS



DIGIMIC lean⁺ is now available in an even more powerful combination: All of the functions of conference technology, in modular construction – in combination with a Vertically Retractable Monitor.

For flexible combination and expansion with the widest variety of data and media connections.

The modular design of DIGIMIC lean⁺ opens up completely new possibilities for the harmonic integration of conference technology with access to data, media connections, and a state-of-the-art monitor into building architecture with a modern design.

The retractable monitor is a true marvel of functionality, engineering & design. All that is visible in the retracted state is the slender brushed steel cover. With a single touch the display panel elevates with a whisper from the housing below.

Designed to encourage interaction within the meeting space it can then disappear as silently & quickly as it appeared to allow the parties' interaction & discourse to continue unobstructed.

DIGIMIC lean⁺ in cooperation with



DIGIMIC Conference Monitor Full HD / Tilt

DIGIMIC lean+ – defined communication.
Speak. Listen. Understand. And Watch!

CMic lean+ CSV has a clearly identifiable button for switching the microphone on or off or for requests to speak.

When switched on, the button will illuminate or flash (for the 'request-to-speak' function) red.

The high-resolution graphical OLED display module has 5 soft key buttons. These buttons can be used for voting or for language selection. Depending on context, the corresponding contents are displayed in the OLED display and can be heard using the headphones.

The language selection information can also be depicted using the respective alphabet (Chinese, Arabic, etc.). The brightness of the display automatically adjusts to the ambient light and offers a glare-free display even in darkened conference halls.

Power outlets, data and media connections can be optionally added.

Available Conference Options

All of the functions of a microphone station can be flexibly combined with one another, arranged and expanded with the widest variety of data, media connections, and power outlets.

Check out:

www.braehler.com/product_configurator.html

Sleek. Silent. Svelte. Handcrafted & tested to ensure the highest standards.

Motorised Screen

Single Touch electronic Anti Clamp Protection

Frame - Aluminium silver anodized

Trim - Black Plexiglass decorative inlay

Chassis & Cartouche - Brushed high-grade steel

Full HD 21.5" LED Backlit TFT

HDCP Compatible

Active Matrix

Widescreen Format

Brightness 250 cd/m²

Contrast Ratio 1000:1

Resolution 1920 x 1080 – Full HD (16:9)

Pixel size 0.1989 x 0.1989 mm

Viewing Angle Horizontal 178°/ Vertical - 178°

Viewing Area

LED Lifespan Up to 50,000 hrs

Video Interface HDMI

Multi Touch Optional

Available Monitor Options

Various display sizes

Double Full HD cam

Custom Colour – Anodization or Coating

Custom Plexiglass Trim Colour

Multi Touch Overlay

Additional sockets – USB / XLR / Phono / Video

Leather Trim

Brähler ICS UK Ltd
Unit2 The Business
Centre
Church End
Cambridge
CB1 3LB

T +44 (0)1223 411 601

F +44 (0)1223 411 602

sales@braehler.co.uk

brähler
www.braehler.co.uk